

POWER DIVIDER (1)

Power Divider	Frequency Range(GHz)	Amplitude Imbalance(dB)	Phase Imbalance (Degrees)	Isolation(dB)	Maximum VSWR	Insertion Loss(dB)	Standard Connectors	Operating Temperatuer	Model Number
2-Way	0.225-0.4	± 0.2	± 2.0	> 25	1.20	< 0.2	SMA Female	-54° to +85° C	PD2-0225-04A
2-Way	0.25-0.5	± 0.2	± 2.0	> 22	1.20	< 0.2	SMA Female	-54° to +85° C	PD2-025-05A
2-Way	0.25-2.0	± 0.3	± 2.5	> 18	1.30	< 1.0	SMA Female	-54° to +85° C	PD2-025-2A
2-Way	0.4-1.0	± 0.2	± 2.0	> 18	1.30	< 0.4	SMA Female	-54° to +85° C	PD2-04-1A
2-Way	0.8-1.0	± 0.3	± 2.0	> 23	1.30	< 0.3	SMA Female	-54° to +85° C	PD2-08-1A
2-Way	0.8-2.2	± 0.2	± 3.0	> 20	1.30	< 0.4	SMA Female	-54° to +85° C	PD2-08-22A
2-Way	0.8-2.5	± 0.3	± 4.0	> 20	1.40	< 0.5	SMA Female	-54° to +85° C	PD2-08-25A
2-Way	0.95-1.225	± 0.3	± 2.0	> 22	1.25	< 0.3	SMA Female	-54° to +85° C	PD2-095-1225A
2-Way	0.5-1.0	± 0.2	± 2.0	> 20	1.25	< 0.3	SMA Female	-54° to +85° C	PD2-05-1A
2-Way	0.5-2.0	± 0.2	± 2.0	> 22	1.30	< 0.6	SMA Female	-54° to +85° C	PD2-05-2A
2-Way	0.5-4.0	± 0.3	± 2.0	> 16	1.40	< 0.5	SMA Female	-54° to +85° C	PD2-05-4A
2-Way	0.5-6.0	± 0.3	± 4.0	> 18	1.40	< 0.6	SMA Female	-54° to +85° C	PD2-05-6A
2-Way	0.5-8.0	± 0.5	± 5.0	> 18	1.50	< 1.0	SMA Female	-54° to +85° C	PD2-05-8A
2-Way	0.5-18.0	± 0.6	± 10.0	> 16	1.50	< 1.7	SMA Female	-54° to +85° C	PD2-05-18A
2-Way	0.5-20.0	± 0.4	± 12.0	> 12	1.80	< 2.2	SMA Female	-54° to +85° C	PD2-05-20A
2-Way	1.0-2.0	± 0.2	± 3.0	> 22	1.30	< 0.3	SMA Female	-54° to +85° C	PD2-1-2A

Power Divider	Frequency Range(GHz)	Amplitude Imbalance(dB)	Phase Imbalance (Degrees)	Isolation(dB)	Maximum VSWR	Insertion Loss(dB)	Standard Connectors	Operating Temperatuer	Model Number
2-Way	1.0-4.0	± 0.2	± 2.0	> 20	1.40	< 0.4	SMA Female	-54° to +85° C	PD2-1-4A
2-Way	1.0-8.0	± 0.3	± 6.0	> 16	1.40	< 1.0	SMA Female	-54° to +85° C	PD2-1-8A
2-Way	1-12.4	± 0.4	± 6.0	> 16	1.40	< 1.5	SMA Female	-54° to +85° C	PD2-1-124A
2-Way	1.0-18.0	± 0.5	± 8.0	> 17	1.60	< 1.5	SMA Female	-54° to +85° C	PD2-1-18A
2-Way	1.5-3.0	± 0.2	± 2.0	> 20	1.30	< 0.3	SMA Female	-54° to +85° C	PD2-15-3A
2-Way	2.0-4.0	± 0.2	± 3.0	> 20	1.30	< 0.4	SMA Female	-54° to +85° C	PD2-2-4A
2-Way	2.0-8.0	± 0.3	± 4.0	> 20	1.40	< 0.4	SMA Female	-54° to +85° C	PD2-2-8A
2-Way	2.0-18.0	± 0.4	± 2.0	> 18	1.40	< 1.0	SMA Female	-54° to +85° C	PD2-2-18B
2-Way	2.0-18.0	± 0.4	± 2.0	> 15	1.40	< 1.0	SMA Female	-54° to +85° C	PD2-2-18C
2-Way	4.0-8.0	± 0.2	± 2.0	> 20	1.40	< 0.4	SMA Female	-54° to +85° C	PD2-4-8A
2-Way	4.0-18.0	± 0.4	± 5.0	> 18	1.50	< 0.8	SMA Female	-54° to +85° C	PD2-4-18A
2-Way	5.0-18.0	± 0.4	± 5.0	> 17	1.40	< 0.5	SMA Female	-54° to +85° C	PD2-5-18A
2-Way	5.8-6.45	± 0.2	± 2.0	> 20	1.30	< 0.3	SMA Female	-54° to +85° C	PD2-58-645A
2-Way	6.0-18.0	± 0.4	± 5.0	> 18	1.50	< 0.7	SMA Female	-54° to +85° C	PD2-6-18A
2-Way	7.2-8.5	± 0.2	± 3.0	> 20	1.40	< 0.5	SMA Female	-54° to +85° C	PD2-72-85A
2-Way	8.0-12.4	± 0.2	± 4.0	> 20	1.35	< 0.4	SMA Female	-54° to +85° C	PD2-8-124A
2-Way	10.0-15.0	± 0.2	± 4.0	> 20	1.40	< 0.4	SMA Female	-54° to +85° C	PD2-10-15A

Power Divider	Frequency Range(GHz)	Amplitude Imbalance(dB)	Phase Imbalance (Degrees)	Isolation(dB)	Maximum VSWR	Insertion Loss(dB)	Standard Connectors	Operating Temperatuer	Model Number
3-Way	2.0-4.0	± 0.4	± 10.0	> 16	1.5	< 0.7	SMA Female	-54° to +85° C	PD3-2-4A
3-Way	2.0-4.0	± 0.4	± 8.0	> 17	1.4	< 0.7	SMA Female	-54° to +85° C	PD3-2-4B
3-Way	2.0-8.0	± 0.8	—	> 18	1.4	< 1.3	SMA Female	-54° to +85° C	PD3-2-8A
3-Way	2.0-18.0	± 0.4	± 10.0	> 18	1.6	< 1.5	SMA Female	-54° to +85° C	PD3-2-18A
4-Way	4.0-8.0	± 0.4	± 8.0	> 16	1.6	< 0.9	SMA Female	-54° to +85° C	PD3-4-8A
4-Way	0.5-1.0	± 0.4	± 5.0	> 22	1.5	< 0.9	SMA Female	-54° to +85° C	PD4-05-1A
4-Way	0.5-2.0	± 0.4	± 6.0	> 20	1.5	< 1.3	SMA Female	-54° to +85° C	PD4-05-2A
4-Way	0.5-2.5	± 0.4	± 6.0	> 20	1.5	< 1.3	SMA Female	-54° to +85° C	PD4-05-25A
4-Way	0.5-3.5	± 0.4	± 8.0	> 20	1.4	< 0.8	SMA Female	-54° to +85° C	PD4-05-35A
4-Way	0.5-6.0	± 0.5	± 8.0	> 17	1.6	< 1.5	SMA Female	-54° to +85° C	PD4-05-6A
4-Way	0.5-8.0	± 0.5	± 6.0	> 18	1.5	< 1.8	SMA Female	-54° to +85° C	PD4-05-8A
4-Way	0.5-18.0	± 0.5	± 8.0	> 16	1.6	< 4.0	SMA Female	-54° to +85° C	PD4-05-18A
4-Way	0.5-20.0	± 0.5	± 8.0	> 15	1.7	< 4.0	SMA Female	-54° to +85° C	PD4-05-20A
4-Way	0.8-2.2	± 0.4	± 6.0	> 20	1.4	< 1.0	SMA Female	-54° to +85° C	PD4-08-22A
4-Way	0.8-2.5	± 0.4	± 8.0	> 20	1.5	< 0.8	SMA Female	-54° to +85° C	PD4-08-25A
4-Way	1.0-2.0	± 0.4	± 6.0	> 20	1.4	< 0.8	SMA Female	-54° to +85° C	PD4-1-2A

Power Divider	Frequency Range(GHz)	Amplitude Imbalance(dB)	Phase Imbalance (Degrees)	Isolation(dB)	Maximum VSWR	Insertion Loss(dB)	Standard Connectors	Operating Temperatuer	Model Number
4-Way	1.0-3.0	± 0.5	± 6.0	> 18	1.5	< 0.9	SMA Female	-54° to +85° C	PD4-1-3A
4-Way	1.0-4.0	± 0.4	± 6.0	> 20	1.5	< 1.0	SMA Female	-54° to +85° C	PD4-1-4A
4-Way	1.0-8.0	± 0.4	± 8.0	> 15	1.5	< 2.0	SMA Female	-54° to +85° C	PD4-1-8A
4-Way	1.0-12.0	± 0.4	± 6.0	> 19	1.5	< 2.0	SMA Female	-54° to +85° C	PD4-1-12A
4-Way	1.0-18.0	± 0.5	± 8.0	> 17	1.6	< 3.6	SMA Female	-54° to +85° C	PD4-1-18A
4-Way	2.0-4.0	± 0.5	± 6.0	> 20	1.4	< 0.6	SMA Female	-54° to +85° C	PD4-2-4A
4-Way	2.0-8.0	± 0.5	± 6.0	> 18	1.45	< 1.0	SMA Female	-54° to +85° C	PD4-2-8A
4-Way	2.0-18.0	± 0.5	± 12.0	> 17	1.7	< 1.8	SMA Female	-54° to +85° C	PD4-2-18A
4-Way	3.0-15.0	± 0.4	± 8.0	> 18	1.4	< 1.0	SMA Female	-54° to +85° C	PD4-3-15A
4-Way	3.62-4.25	± 0.5	± 6.0	> 19	1.35	< 0.6	SMA Female	-54° to +85° C	PD4-362-425A
4-Way	4.0-8.0	± 0.5	± 6.0	> 19	1.45	< 0.6	SMA Female	-54° to +85° C	PD4-4-8A
4-Way	5.0-18.0	± 0.5	± 8.0	> 16	1.6	< 1.2	SMA Female	-54° to +85° C	PD4-5-18A
4-Way	5.8-6.45	± 0.5	± 6.0	> 19	1.35	< 0.6	SMA Female	-54° to +85° C	PD4-58-645A
4-Way	6.0-18.0	± 0.5	± 8.0	> 18	1.6	< 1.3	SMA Female	-54° to +85° C	PD4-6-18A
4-Way	7.2-8.5	± 0.5	± 8.0	> 18	1.45	< 1.0	SMA Female	-54° to +85° C	PD4-72-85A
4-Way	8.0-12.4	± 0.5	± 6.0	> 16	1.45	< 0.8	SMA Female	-54° to +85° C	PD4-8-124A
4-Way	8.0-15.0	± 0.5	± 8.0	> 16	1.5	< 1.0	SMA Female	-54° to +85° C	PD4-8-15A