

POWER DIVIDER (2)

Power Divider	Frequency Range(GHz)	Amplitude Imbalance(dB)	Phase Imbalance (Degrees)	Isolation(dB)	Maximum VSWR	Insertion Loss(dB)	Standard Connectors	Operating Temperatuer	Model Number
6-Way	2.0-4.0	± 0.5	± 4.0	> 17	1.6	< 1.7	SMA Female	-54° to +85° C	PD6-2-4A
6-Way	2.0-8.0	± 1.0	± 8.0	> 17	1.4	< 1.6	SMA Female	-54° to +85° C	PD6-2-8A
6-Way	2.0-18.0	± 0.8	± 10.0	> 15	2.0	< 2.5	SMA Female	-54° to +85° C	PD6-2-18A
6-Way	4.0-8.0	± 0.6	± 5.0	> 16	1.7	< 2.0	SMA Female	-54° to +85° C	PD6-4-8A
8-Way	0.5-1.0	± 0.4	± 5.0	> 20	1.3	< 0.8	SMA Female	-54° to +85° C	PD8-05-1A
8-Way	0.5-2.0	± 0.6	± 8.0	> 18	1.5	< 1.0	SMA Female	-54° to +85° C	PD8-05-2A
8-Way	0.5-6.0	± 0.4	± 8.0	> 20	1.4	< 1.5	SMA Female	-54° to +85° C	PD8-05-6A
8-Way	0.5-8.0	± 0.8	± 10.0	> 18	1.6	< 2.6	SMA Female	-54° to +85° C	PD8-05-8A
8-Way	0.8-2.2	± 0.6	± 8.0	> 18	1.5	< 1.0	SMA Female	-54° to +85° C	PD8-08-22A
8-Way	0.85-1.7	± 0.4	± 5.0	> 20	1.3	< 0.8	SMA Female	-54° to +85° C	PD8-085-17A
8-Way	1.0-2.0	± 0.4	± 5.0	> 20	1.35	< 0.8	SMA Female	-54° to +85° C	PD8-1-2A
8-Way	1.0-3.0	± 0.6	± 8.0	> 16	1.5	< 1.0	SMA Female	-54° to +85° C	PD8-1-3A
8-Way	2.0-4.0	± 0.4	± 5.0	> 18	1.45	< 0.8	SMA Female	-54° to +85° C	PD8-2-4A
8-Way	2.0-8.0	± 0.7	± 10.0	> 16	1.6	< 1.4	SMA Female	-54° to +85° C	PD8-2-8A
8-Way	2.0-18.0	± 0.6	± 15.0	> 15	1.7	< 2.2	SMA Female	-54° to +85° C	PD8-2-18A

Power Divider	Frequency Range(GHz)	Amplitude Imbalance(dB)	Phase Imbalance (Degrees)	Isolation(dB)	Maximum VSWR	Insertion Loss(dB)	Standard Connectors	Operating Temperatuer	Model Number
8-Way	4.0-8.0	± 0.6	± 10.0	>17	1.6	< 1.4	SMA Female	-54° to +85° C	PD8-4-8A
8-Way	4.0-18.0	± 0.6	± 10.0	>15	1.8	< 2.5	SMA Female	-54° to +85° C	PD8-4-18A
8-Way	3.0-15.0	± 0.5	± 12.0	>15	1.8	< 1.3	SMA Female	-54° to +85° C	PD8-3-15A
8-Way	5.0-18.0	± 0.5	± 12.0	>15	1.7	< 1.5	SMA Female	-54° to +85° C	PD8-5-18A
8-Way	5.8-6.4	± 0.6	± 8.0	> 18	1.4	< 1.0	SMA Female	-54° to +85° C	PD8-58-64A
8-Way	6.0-18.0	± 0.8	± 10.0	> 17	1.8	< 2.0	SMA Female	-54° to +85° C	PD8-6-18A
8-Way	7.2-8.5	± 0.5	± 10.0	>20	1.6	< 1.3	SMA Female	-54° to +85° C	PD8-72-85A
8-Way	8.0-12.0	± 0.2	± 5.0	>20	1.5	< 1.0	SMA Female	-54° to +85° C	PD8-8-12A
8-Way	8.0-14.0	± 0.5	± 12.0	>16	1.7	< 1.3	SMA Female	-54° to +85° C	PD8-8-14A
12-Way	2.0-8.0	± 1.0	± 7.0	>16	1.6	< 2.2	SMA Female	-54° to +85° C	PD12-2-8A
12-Way	8.0-18.0	± 1.0	± 10.0	>15	1.8	< 2.5	SMA Female	-54° to +85° C	PD12-8-18A
16-Way	0.8-2.5	± 0.4	± 8.0	> 18	1.5	< 1.7	SMA Female	-54° to +86° C	PD16-08-25A