

DIRECTIONAL COUPLERS

Model Number	Frequency Range(GHz)	Coupling(dB)	Frequency Sensitivity(dB)	Maximum VSWR	Insertion LOSS(dB)	Directivity (dB)	Standard Connectors	Operating Temperat
C0518-10A	0.5-18	10±1	±0.7	1.50	≤ 1.5	10	SMA Female	-55 - +85
C0518-20A	0.5-18	20±1	±0.7	1.50	≤ 1.0	10	SMA Female	-55 - +85
C0518-30A	0.5-18	30±1	±0.7	1.50	≤ 1.0	10	SMA Female	-55 - +85
C0727-6A	0.7-2.7	6±1	±0.7	1.20	≤ 05	20	SMA Female	-55 - +85
C0727-10A	0.7-2.7	10±1	±0.7	1.20	≤ 05	20	SMA Female	-55 - +85
C0727-20A	0.7-2.7	20±1	±0.7	1.20	≤ 04	20	SMA Female	-55 - +85
C0727-30A	0.7-2.7	30±1	±0.7	1.20	≤ 04	20	SMA Female	-55 - +85
C14-6A	1.0-4.0	6±1	±0.7	1.20	≤ 05	20	SMA Female	-55 - +85
C14-10A	1.0-4.0	10±1	±0.7	1.20	≤ 05	20	SMA Female	-55 - +85
C14-20A	1.0-4.0	20±1	±0.7	1.20	≤ 04	20	SMA Female	-55 - +85
C14-30A	1.0-4.0	30±1	±0.7	1.20	≤ 04	20	SMA Female	-55 - +85
C118-10A	1.0-18	10±1	±0.7	1.50	≤ 1.3	12	SMA Female	-55 - +85
C118-20A	1.0-18	20±1	±0.7	1.50	≤ 0.9	12	SMA Female	-55 - +85
C118-30A	1.0-18	30±1	±0.7	1.50	≤ 0.9	12	SMA Female	-55 - +85
C28-6A	2.0-8	6±1	±0.7	1.30	≤ 05	20	SMA Female	-55 - +85
C28-10A	2.0-8	10±1	±0.7	1.30	≤ 05	20	SMA Female	-55 - +85
C28-20A	2.0-8	20±1	±0.7	1.30	≤ 05	20	SMA Female	-55 - +85
C28-30A	2.0-8	30±1	±0.7	1.30	≤ 05	18	SMA Female	-55 - +85
C218-10A	2.0-18	10±1	±0.5	1.50	≤ 1.1	12	SMA Female	-55 - +85
C218-20A	2.0-18	20±1	±0.5	1.50	≤ 0.8	12	SMA Female	-55 - +85
C218-30A	2-18	30±1	±0.5	1.50	≤ 0.7	12	SMA Female	-55 - +85
C418-10A	4-18	10±1	±0.5	1.50	≤ 1.0	12	SMA Female	-55 - +85
C418-20A	4-18	20±1	±0.5	1.50	≤ 0.7	12	SMA Female	-55 - +85
C418-30A	4-18	30±1	±0.5	1.50	≤ 0.7	12	SMA Female	-55 - +85